# Nov-2024 Get Totally Free Updates on H13-511\_V5.5 Dumps PDF Questions [Q145-Q161



Nov-2024 Get Totally Free Updates on H13-511\_V5.5 Dumps PDF Questions Prepare With Top Rated High-quality H13-511\_V5.5 Dumps For Success in H13-511\_V5.5 Exam NEW QUESTION 145

In a distributed storage system, in the face of high-performance real-time processing scenarios of large amounts of data, SSDs can be used instead of HDDs, and ln niBan networks can be used instead of GE/10GE networks to meet the requirements.

- \* True
- \* False

## **NEW QUESTION 146**

The Elastic Cloud Server supports the use of secret keys for authentication. It is necessary to parse the secret key file used when creating the Elastic Cloud Server into a password through the password acquisition function provided by the management console.

- \* True
- \* False

# **NEW QUESTION 147**

Which of the following devices form a communication network?

- \* router
- \* switch
- \* firewall

\* server

## **NEW QUESTION 148**

Which of the following descriptions about IP routing is wrong?

- \* Include the next MAC address
- \* Can be dynamically generated
- \* Include the outgoing interface name
- \* Can be manually configured

## **NEW QUESTION 149**

In Huawei FusionCompute, the virtual network card of each virtual machine is connected to the port of the virtual switch. In order to facilitate the user to configure and manage multiple ports at the same time, the ports with the same network attributes are divided into the same port group.

- \* True
- \* False

# **NEW QUESTION 150**

Which of the following are the advantages of cloud monitoring service CES? (Multiple choice)

- \* Raw sampling data is reported in real time, providing real-time monitoring of cloud services, triggering alarms in real time and notifying users
- \* The cloud monitoring service is automatically activated, and it is convenient to view the service running status and set alarm rules
- \* When the status of the cloud service triggers an alarm, the cloud monitoring service can automatically recover from the alarm through a pre-set mechanism
- \* By enabling the message notification service in the alarm rule, the user can know the business alarm information at the first time

## **NEW QUESTION 151**

The reliability of Huawei's desktop cloud system solution is achieved through the reliability of management nodes and user connection reliability. Management node reliability is guaranteed from hardware reliability, operating system reliability, software process reliability, etc. User connection reliability is guaranteed from client disconnection reconnection, port anti-conflict, etc.

- \* True
- \* False

# **NEW QUESTION 152**

Memory bubbles refer to virtualizing external storage resources into memory for use by virtual machines, and storing temporarily unused data on virtual machines on external storage.

- \* True
- \* False

## **NEW QUESTION 153**

Which of the following items are wrong in the description of the IAAS model? (Multiple choice)

- \* Higher flexibility than other deployment modes
- \* Users need to install virtualization transparent connection for resource integration
- \* Compared with other deployment modes, the degree of automation is higher
- \* Users need to install upper-layer applications to carry services

## **NEW QUESTION 154**

In FusionAccess, which of the following descriptions about linked clone virtual machines are correct? (Multiple choice)

- \* Linked clone virtual machines support rapid provisioning in batches
- \* The linked clone virtual machine logically combines the master disk and the differential disk into a linked clone disk, which is used as the virtual machine system disk
- \* Linked-clone desktop groups support "pooled" and "dedicated" types
- \* Linked clone virtual machine templates need to add domains, but do not need to encapsulate the system

## **NEW QUESTION 155**

Which of the following items belong to the underlying virtualization core module provided for the processor in the KVM architecture? (Multiple choice)

- \* kvm.vm
- \* kvm.ko
- \* kvm-amd. ko
- \* kvm-intel.ko

## **NEW QUESTION 156**

In Huawei FusionCompute, the function that disk thin provisioning can achieve is? (Multiple choice)

- \* Virtual storage thin provisioning has nothing to do with the operating system and hardware, so as long as the virtual image management system is used, disk thin provisioning can be realized
- \* Provide virtual disk space monitoring and recycling functions
- \* Recycling virtual machine disks in NTFS format is currently not supported
- \* Provide early warning of data storage capacity, you can set the threshold, and generate an alarm when the storage capacity exceeds the threshold

## **NEW QUESTION 157**

Which of the following descriptions about the conditions for creating virtual machine snapshots is wrong?

- \* The storage type of the virtual machine disk is FusionStorage Block, virtualized local hard disk, virtualized SAN storage or ArLJ0urBENAS storage
- \* The available capacity of the data storage where the virtual machine is located is sufficient
- \* During the process of creating a snapshot, the disk expansion operation cannot be performed on the virtual machine
- \* There is no need to install Toos before creating a snapshot of the virtual machine

## **NEW QUESTION 158**

In the CPU hardware-assisted virtualization, the newly added execution mode is (), and the VRM selects an available host according to the specification information of the saved virtual machine.

root mode

## **NEW QUESTION 159**

Which of the following descriptions about network virtualization are correct? (Multiple choice)

\* When the virtual machine communicates with the external network, the NAT gateway will convert the source IP address in the data packet into the address of the physical bridge, and generate a record, and forward the data packet to the corresponding virtual machine according to this record

This page was exported from -  $\underline{Exams\ Labs\ Braindumps}$  Export date: Mon Dec 23 19:30:46 2024 / +0000 GMT

- \* If the DVS port group type is normal, only one VLAN ID can be configured
- \* When running the multicast service, you only need to enable the IGMP Snooping switch on the DVS, and you don't need to enable the IGMP snooping function of the switch and the querier function of the device on the multicast channel
- \* A physical network card that supports SRIOV can virtualize multiple virtual network cards for use by virtual machines

## **NEW QUESTION 160**

Which of the following technologies or devices cannot isolate broadcasting?

- \* Router
- \* Firewall
- \* Hub
- \* VLAN

# **NEW QUESTION 161**

Which class of IPv4for address is is used for multicast?

- \* Class A
- \* Class B
- \* Class D
- \* Class C

Get 100% Success with Latest HCIA-Cloud Computing H13-511\_V5.5 Exam Dumps: https://www.examslabs.com/Huawei/HCIA-Cloud-Computing/best-H13-511\_V5.5-exam-dumps.html]